

TUYAU PNEUMATIQUE EN PVC SOUPLE ET RACCORD RAPIDE



Super flexible, robuste et renforcé -
Idéal pour les installations pneumatiques.
Matière : 3 couches de PVC renforcé par de la fibre polyester.

Pression de travail max. : 15 bar à 20°C.

Température d'utilisation : de - 20°C à + 60°C.

Ref. JWL.xxx30... Avec raccord rapide Ref. JWL.530
(modèle EURO avec anneau de retenue en acier trempé galvanisé + embout pour dito)

Ref. JWL.xxx20... Avec raccord rapide Ref. JWL.520
(modèle EURO avec anneau de retenue en plastique + embout pour dito)



dimensions	longueur de travail	Ref.	
		avec raccord JWL.530	avec raccord JWL.520
ø 6,3 x 11	5	<i>JWL.1002.05530</i>	<i>JWL.1002.05520</i>
ø 6,3 x 11	10	<i>JWL.1002.10530</i>	<i>JWL.1002.10520</i>
ø 6,3 x 11	15	<i>JWL.1002.15530</i>	<i>JWL.1002.15520</i>
ø 6,3 x 11	20	<i>JWL.1002.20530</i>	<i>JWL.1002.20520</i>
ø 9 x 14,5	5	<i>JWL.1004.05530</i>	<i>JWL.1004.05520</i>
ø 9 x 14,5	10	<i>JWL.1004.10530</i>	<i>JWL.1004.10520</i>
ø 9 x 14,5	15	<i>JWL.1004.15530</i>	<i>JWL.1004.15520</i>
ø 9 x 14,5	20	<i>JWL.1004.20530</i>	<i>JWL.1004.20520</i>



TUYAU SPIRALE PNEUMATIQUE EN NYLON



Modèle en Nylon PA 12 - 1/4" BSPT mâle

Modèle très robuste, très résistant à la température avec une force de rappel importante
Manutention aisée tout en épargnant la place.

Ce tuyau reste endommagé en cas de "croquage"

Ne pas exposer au soleil continuellement.

Caractéristiques techniques :

Pression max. : 25 bar à 23°C.

Pour température : - 40° à + 100°C.

Dureté en surface : 63 Sh D

Avec raccords tournants 1/4"

Dimensions : Ø 6 x Ø 8 mm

Sur demande :

autre dimensions : Ø 7,5 x Ø 10 mm

autre filetage : 1/2" BSPT



1/4" BSPT EXTERIEUR

dimensions (mm)	longueur de travail (m)	Ref.
Ø 6 x Ø 8	2,5	JWL.1700208.02
Ø 6 x Ø 8	3,5	JWL.1700208.03
Ø 6 x Ø 8	5	JWL.1700208.04
Ø 6 x Ø 8	7,5	JWL.1700208.05
Ø 6 x Ø 8	10	JWL.1700208.06
Ø 6 x Ø 8	15	JWL.1700208.07



Modèle en polyuréthane PUR – 1/4" BSPT - mâle

Modèle résistant, très souple et élastique.

Pas de déformation après un "croquage"

Pas de détérioration de pièces peintes

Plus petit diamètre de spirale

Ne pas exposer au soleil continuellement.

Caractéristiques techniques :

Pression max. : 10 bar à 20°C.

Pour températures de - 40° à + 60°C.

Avec raccords fixes

Dimensions : Ø 5 x Ø 8 mm

Sur demande :

autres dimensions : Ø 4 x Ø 6 mm

autres filetages : 3/8" et 1/2" BSPT

1/4" BSPT EXTERIEUR

dimensions (mm)	longueur de travail (m)	Ref.
Ø 5 x Ø 8	2	JWL.1710208.02
Ø 5 x Ø 8	4	JWL.1710208.04
Ø 5 x Ø 8	6	JWL.1710208.06
Ø 5 x Ø 8	8	JWL.1710208.08

FITTINGS POUR INSTALLATION D'AIR COMPRI ME



RACCORD A ROTULE

dimensions (mm)	Ref.
Coupler plug (Euro) x 1/4" internal thread	JWL.443302
Coupler plug (Euro) x 1/4" external thread	JWL.443312
1/4" internal x 1/4" internal thread	JWL.440202
1/4" external x 1/4" internal thread	JWL.441202
3/8" external x 3/8" internal thread	JWL.441404
1/4" hose connection x 1/4" internal thread	JWL.442202
1/4" hose connection x 1/4" external thread	JWL.442212
3/8" hose connection x 1/4" external thread	JWL.442412
3/8" hose connection x 3/8" external thread	JWL.442414
PUR connection ø5/ø8 mm x 1/4" ext. thread	JWL.440812
PUR connection ø6,5/ø10 mm x 1/4" ext. thread	JWL.441012



ROBINET A BILLE

dimensions (mm)	Ref.
1/4" internal thread x 1/4" internal thread	JWL.631022
3/8" internal thread x 3/8" internal thread	JWL.631044
1/2" internal thread x 1/2" internal thread	JWL.631055
1/4" ext. thread x 1/4" internal thread	JWL.631222
3/8" ext. thread x 3/8" internal thread	JWL.631244
1/2" ext. thread x 1/2" internal thread	JWL.631255



REDUCTEUR DE PAS

dimensions (mm)	Ref.
1/8" ext. x 1/8" internal thread	JWL.622000
1/8" ext. x 1/4" internal thread	JWL.622002
1/8" ext. x 3/8" internal thread	JWL.622004
1/8" ext. x 1/2" internal thread	JWL.622005
1/4" ext. x 1/8" internal thread	JWL.622020
1/4" ext. x 1/4" internal thread	JWL.622022
1/4" ext. x 3/8" internal thread	JWL.622024
1/4" ext. x 1/2" internal thread	JWL.622025
3/8" ext. x 1/8" internal thread	JWL.622040
3/8" ext. x 1/4" internal thread	JWL.622042
3/8" ext. x 3/8" internal thread	JWL.622044
3/8" ext. x 1/2" internal thread	JWL.622045
1/2" ext. x 1/8" internal thread	JWL.622050
1/2" ext. x 1/4" internal thread	JWL.622052
1/2" ext. x 3/8" internal thread	JWL.622054
1/2" ext. x 1/2" internal thread	JWL.622055
1/2" ext. x 3/4" internal thread	JWL.622057
3/4" ext. x 3/8" internal thread	JWL.622074
3/4" ext. x 1/2" internal thread	JWL.622075



ADAPTATEUR

dimensions (mm)	Ref.
1/8" ext. x 1/8" external thread	JWL.624000
1/8" ext. x 1/4" external thread	JWL.624002
1/8" ext. x 3/8" external thread	JWL.624004
1/4" ext. x 1/4" external thread	JWL.624022
1/4" ext. x 3/8" external thread	JWL.624024
1/4" ext. x 1/2" external thread	JWL.624025
3/8" ext. x 3/8" external thread	JWL.624044
3/8" ext. x 1/2" external thread	JWL.624045
1/2" ext. x 1/2" external thread	JWL.624055
1/2" ext. x 3/4" external thread	JWL.624057
3/4" ext. x 3/4" external thread	JWL.624077



PIECE EN "L"

dimensions (mm)	Ref.
1/8" int. x 1/8" internal thread	JWL.623000
1/4" int. x 1/4" internal thread	JWL.623022
3/8" int. x 3/8" internal thread	JWL.623044
1/2" int. x 1/2" internal thread	JWL.623055
3/4" int. x 3/4" internal thread	JWL.623077
1/8" ext. x 1/8" external thread	JWL.623100
1/4" ext. x 1/4" external thread	JWL.623122
3/8" ext. x 3/8" external thread	JWL.623144
1/2" ext. x 1/2" external thread	JWL.623155
1/8" ext. x 1/8" internal thread	JWL.623200
1/4" ext. x 1/4" internal thread	JWL.623222
3/8" ext. x 3/8" internal thread	JWL.623244
1/2" ext. x 1/2" internal thread	JWL.623255
3/4" ext. x 3/4" internal thread	JWL.623277

FITTINGS POUR INSTALLATION D'AIR COMPRI ME



PIECE EN "T"

dimensions (mm)	Ref.
1/8" x 1/8" x 1/8" internal thread	JWL.630000
1/4" x 1/4" x 1/4" internal thread	JWL.630022
3/8" x 3/8" x 3/8" internal thread	JWL.630044
1/2" x 1/2" x 1/2" internal thread	JWL.630055
1/8" ext. x 1/8" int. x 1/8" internal thread	JWL.630200
1/4" ext. x 1/4" int. x 1/4" internal thread	JWL.630222
3/8" ext. x 3/8" int. x 3/8" internal thread	JWL.630244
1/2" ext. x 1/2" int. x 1/2" internal thread	JWL.630255



PIECE EN "Y"

dimensions (mm)	Ref.
1/8" x 1/8" x 1/8" internal thread	JWL.627000
1/4" x 1/4" x 1/4" internal thread	JWL.627022
3/8" x 3/8" x 3/8" internal thread	JWL.627044
1/2" x 1/2" x 1/2" internal thread	JWL.627055
1/8" ext. x 1/8" int. x 1/8" internal thread	JWL.627200
1/4" ext. x 1/4" int. x 1/4" internal thread	JWL.627222
3/8" ext. x 3/8" int. x 3/8" internal thread	JWL.627244
1/2" ext. x 1/2" int. x 1/2" internal thread	JWL.627255



PIECE EN "X"

dimensions (mm)	Ref.
4 x 1/8" internal thread	JWL.628000
4 x 1/4" internal thread	JWL.628022
4 x 3/8" internal thread	JWL.628044
4 x 1/2" internal thread	JWL.628055



CONNECTEUR POUR TUYAU

dimensions (mm)	Ref.
3/16" - 5 mm x 1/8" external thread	JWL.625000
3/16" - 5 mm x 1/4" external thread	JWL.625002
1/4" - 6 mm x 1/8" external thread	JWL.625020
1/4" - 6 mm x 1/4" external thread	JWL.625022
1/4" - 6 mm x 3/8" external thread	JWL.625024
1/4" - 6 mm x 1/2" external thread	JWL.625025
5/16" - 8 mm x 1/4" external thread	JWL.625032
5/16" - 8 mm x 3/8" external thread	JWL.625034
5/16" - 8 mm x 1/2" external thread	JWL.625035
3/8" - 10 mm x 1/4" external thread	JWL.625042
3/8" - 10 mm x 3/8" external thread	JWL.625044
3/8" - 10 mm x 1/2" external thread	JWL.625045
1/2" - 13 mm x 1/4" external thread	JWL.625052
1/2" - 13 mm x 3/8" external thread	JWL.625054
1/2" - 13 mm x 1/2" external thread	JWL.625055
1/2" - 13 mm x 3/4" external thread	JWL.625057
3/4" - 20 mm x 3/8" external thread	JWL.625074
3/4" - 20 mm x 3/4" external thread	JWL.625077
1/4" - 6 mm x 1/8" internal thread	JWL.626020
1/4" - 6 mm x 1/4" internal thread	JWL.626022
1/4" - 6 mm x 3/8" internal thread	JWL.626024
5/16" - 8 mm x 1/4" internal thread	JWL.626032
3/8" - 10 mm x 1/4" internal thread	JWL.626042
3/8" - 10 mm x 3/8" internal thread	JWL.626044
3/8" - 10 mm x 1/2" internal thread	JWL.626045
1/2" - 13 mm x 1/4" internal thread	JWL.626052
1/2" - 13 mm x 3/8" internal thread	JWL.626054
1/2" - 13 mm x 1/2" internal thread	JWL.626055



DOUILLE TARAUEDE

dimensions (mm)	Ref.
1/8" internal thread x 1/8" internal thread	JWL.629000
1/8" internal thread x 1/4" internal thread	JWL.629002
1/8" internal thread x 3/8" internal thread	JWL.629004
1/4" internal thread x 1/4" internal thread	JWL.629022
1/4" internal thread x 3/8" internal thread	JWL.629024
1/4" internal thread x 1/2" internal thread	JWL.629025
3/8" internal thread x 3/8" internal thread	JWL.629044
3/8" internal thread x 1/2" internal thread	JWL.629045
1/2" internal thread x 1/2" internal thread	JWL.629055
3/4" internal thread x 1/2" internal thread	JWL.629075
3/4" internal thread x 3/4" internal thread	JWL.629077



CONNECTEUR POUR TUYAU

dimensions (mm)	Ref.
1/4" (6mm) x 1/4" (6mm)	JWL.621022
5/16" (8mm) x 5/16" (8mm)	JWL.621033
3/8" (10mm) x 3/8" (10mm)	JWL.621044
1/2" (12mm) x 1/2" (12mm)	JWL.621055