

BAGUE RECEPTRICE POUR INDEX

H.22110...



MATIERE : acier nitruré.

REMARQUE :

Bague rapportée pour les blocs-support Ref. H.22110.0412 et 0416.

Température d'utilisation : max 250°C.

| d1 | d2 + 0,1 alésage | pour boulon Ø | d3 +/- 0,3 | l1 min. | l2 - 0,3 | l3 | SW | Ref. |
|-----------|---------------------|---------------|---------------|------------|----------|----|----|--------------|
| M12 x 1,5 | 4,2 | 4 | 12,1 | 9 | 12 | 15 | 13 | H.22110.0454 |
| M12 x 1,5 | 5,2 | 5 | 12,1 | 9 | 12 | 15 | 13 | H.22110.0455 |
| M12 x 1,5 | 6,2 | 6 | 12,1 | 9 | 12 | 13 | 13 | H.22110.0456 |
| M16 x 1,5 | 8,2 | 8 | 16,1 | 11 | 14 | 15 | 17 | H.22110.0458 |
| M16 x 1,5 | 10,2 | 10 | 16,1 | 11 | 14 | 15 | 17 | H.22110.0460 |
| M16 x 1,5 | 12,2 | 12 | 16,1 | 11 | 14 | 15 | 17 | H.22110.0462 |

