

PNEUMATISCHE SLANG UIT SOEPEL PVC



Super flexibel, robuust en versterkt – ideaal voor pneumatische installaties.

Materiaal : 3 PVC lagen, versterkt met polyestervezel

Max. werkingsdruk : 15 bar à 20°C.

Gebruikstemperatuur : van – 20°C tot + 60°C.

Ref. JWL.xxx30... = met snelle koppeling Ref. JWL.530 (model EURO met stelling uit staal gehard en verzinkt + nippel voor dito)

Ref. JWL.xxx20... = met snelle koppeling Ref. JWL.520 (model EURO met stelling uit kunststof + nippel voor dito)



afmetingen	werklenkte	Ref.	
		met koppeling JWL.530	met koppeling JWL.520
ø 6,3 x 11	5	JWL.1002.05530	JWL.1002.05520
ø 6,3 x 11	10	JWL.1002.10530	JWL.1002.10520
ø 6,3 x 11	15	JWL.1002.15530	JWL.1002.15520
ø 6,3 x 11	20	JWL.1002.20530	JWL.1002.20520
ø 9 x 14,5	5	JWL.1004.05530	JWL.1004.05520
ø 9 x 14,5	10	JWL.1004.10530	JWL.1004.10520
ø 9 x 14,5	15	JWL.1004.15530	JWL.1004.15520
ø 9 x 14,5	20	JWL.1004.20530	JWL.1004.20520



PNEUMATISCHE SKUNSTSTOFFEN SPIRAASLANG



Model uit Nylon PA 12 - 1/4" BSPT male

Zeer robuust model, zeer temperatuurbestendig met een belangrijke terugslagkracht.
Eenvoudig hantereerbaar met plaatsbesparend
Deze slang wordt gekeurd bij het knikken ervan
Geen voortdurende blootstelling aan zonlicht

Technische kenmerken :

Max. druk . : 25 bar bij 23°C.
Voor temperaturen : van - 40° tot + 100°C.
Oppervlaktehardheid : 63 Sh D

Met draaiende koppeling 1/4"

Afmetingen : Ø 6 x Ø 8 mm
Op aanvraag :
andere afmetingen : Ø 7,5 x Ø 10 mm
andere schroefdraad 1/2" BSPT



1/4" BSPT BUITENSCHROEFDRAAD

afmetingen (mm)	werklengthe (m)	Ref.
Ø 6 x Ø 8	2,5	JWL.1700208.02
Ø 6 x Ø 8	3,5	JWL.1700208.03
Ø 6 x Ø 8	5	JWL.1700208.04
Ø 6 x Ø 8	7,5	JWL.1700208.05
Ø 6 x Ø 8	10	JWL.1700208.06
Ø 6 x Ø 8	15	JWL.1700208.07



Model uit polyurétaan PUR - 1/4" BSPT - male

Zeer soepel en elastisch model.
Geen blijvende beschadiging kreuken nat het knikken
Geen gevaar voor beschadiging van gelakte stukken,
Kleinere spiraal diameter
Geen voortdurende blootstelling aan zonlicht

Technische kenmerken :

Max druk . : 10 bar bij 20°C.
Voor temperaturen : van - 40° tot + 60°C.

Met vaste koppelingen

Afmetingen : Ø 5 x Ø 8 mm
Opaanvraag : :
andere afmetingen : Ø 4 x Ø 6,5 mm
andere schroefdraad : 3/8" et 1/2" BSPT

1/4" BSPT BUITENSCHROEFDRAAD

afmetingen (mm)	werklengthe (m)	Ref.
Ø 5 x Ø 8	2	JWL.1710208.02
Ø 5 x Ø 8	4	JWL.1710208.04
Ø 5 x Ø 8	6	JWL.1710208.06
Ø 5 x Ø 8	8	JWL.1710208.08

FITTINGS VOOR PERSLUCHTINSTALLATIE



KOGELKOPPELSTUK

afmetingen (mm)	Ref.
Coupler plug (Euro) x 1/4" internal thread	JWL.443302
Coupler plug (Euro) x 1/4" external thread	JWL.443312
1/4" internal x 1/4" internal thread	JWL.440202
1/4" external x 1/4" internal thread	JWL.441202
3/8" external x 3/8" internal thread	JWL.441404
1/4" hose connection x 1/4" internal thread	JWL.442202
1/4" hose connection x 1/4" external thread	JWL.442212
3/8" hose connection x 1/4" external thread	JWL.442412
3/8" hose connection x 3/8" external thread	JWL.442414
PUR connection ø5/ø8 mm x 1/4" ext. thread	JWL.440812
PUR connection ø6,5/ø10 mm x 1/4" ext. thread	JWL.441012



SCHROEFDRAAD REDUCTORSTUK

afmetingen (mm)	Ref.
1/8" ext. x 1/8" internal thread	JWL.622000
1/8" ext. x 1/4" internal thread	JWL.622002
1/8" ext. x 3/8" internal thread	JWL.622004
1/8" ext. x 1/2" internal thread	JWL.622005
1/4" ext. x 1/8" internal thread	JWL.622020
1/4" ext. x 1/4" internal thread	JWL.622022
1/4" ext. x 3/8" internal thread	JWL.622024
1/4" ext. x 1/2" internal thread	JWL.622025
3/8" ext. x 1/8" internal thread	JWL.622040
3/8" ext. x 1/4" internal thread	JWL.622042
3/8" ext. x 3/8" internal thread	JWL.622044
3/8" ext. x 1/2" internal thread	JWL.622045
1/2" ext. x 1/8" internal thread	JWL.622050
1/2" ext. x 1/4" internal thread	JWL.622052
1/2" ext. x 3/8" internal thread	JWL.622054
1/2" ext. x 1/2" internal thread	JWL.622055
1/2" ext. x 3/4" internal thread	JWL.622057
3/4" ext. x 3/8" internal thread	JWL.622074
3/4" ext. x 1/2" internal thread	JWL.622075



KOGELKRAAN

afmetingen (mm)	Ref.
1/4" internal thread x 1/4" internal thread	JWL.631022
3/8" internal thread x 3/8" internal thread	JWL.631044
1/2" internal thread x 1/2" internal thread	JWL.631055
1/4" ext. thread x 1/4" internal thread	JWL.631222
3/8" ext. thread x 3/8" internal thread	JWL.631244
1/2" ext. thread x 1/2" internal thread	JWL.631255



ADAPTATORSTUK

afmetingen (mm)	Ref.
1/8" ext. x 1/8" external thread	JWL.624000
1/8" ext. x 1/4" external thread	JWL.624002
1/8" ext. x 3/8" external thread	JWL.624004
1/4" ext. x 1/4" external thread	JWL.624022
1/4" ext. x 3/8" external thread	JWL.624024
1/4" ext. x 1/2" external thread	JWL.624025
3/8" ext. x 3/8" external thread	JWL.624044
3/8" ext. x 1/2" external thread	JWL.624045
1/2" ext. x 1/2" external thread	JWL.624055
1/2" ext. x 3/4" external thread	JWL.624057
3/4" ext. x 3/4" external thread	JWL.624077



L - STUK

afmetingen (mm)	Ref.
1/8" int. x 1/8" internal thread	JWL.623000
1/4" int. x 1/4" internal thread	JWL.623022
3/8" int. x 3/8" internal thread	JWL.623044
1/2" int. x 1/2" internal thread	JWL.623055
3/4" int. x 3/4" internal thread	JWL.623077
1/8" ext. x 1/8" external thread	JWL.623100
1/4" ext. x 1/4" external thread	JWL.623122
3/8" ext. x 3/8" external thread	JWL.623144
1/2" ext. x 1/2" external thread	JWL.623155
1/8" ext. x 1/8" internal thread	JWL.623200
1/4" ext. x 1/4" internal thread	JWL.623222
3/8" ext. x 3/8" internal thread	JWL.623244
1/2" ext. x 1/2" internal thread	JWL.623255
3/4" ext. x 3/4" internal thread	JWL.623277

FITTINGS VOOR PERSLUCHTINSTALLATIE



T - STUK

afmetingen (mm)	Ref.
1/8" x 1/8" x 1/8" internal thread	JWL.630000
1/4" x 1/4" x 1/4" internal thread	JWL.630022
3/8" x 3/8" x 3/8" internal thread	JWL.630044
1/2" x 1/2" x 1/2" internal thread	JWL.630055
1/8" ext. x 1/8" int. x 1/8" internal thread	JWL.630200
1/4" ext. x 1/4" int. x 1/4" internal thread	JWL.630222
3/8" ext. x 3/8" int. x 3/8" internal thread	JWL.630244
1/2" ext. x 1/2" int. x 1/2" internal thread	JWL.630255



Y STUK

afmetingen (mm)	Ref.
1/8" x 1/8" x 1/8" internal thread	JWL.627000
1/4" x 1/4" x 1/4" internal thread	JWL.627022
3/8" x 3/8" x 3/8" internal thread	JWL.627044
1/2" x 1/2" x 1/2" internal thread	JWL.627055
1/8" ext. x 1/8" int. x 1/8" internal thread	JWL.627200
1/4" ext. x 1/4" int. x 1/4" internal thread	JWL.627222
3/8" ext. x 3/8" int. x 3/8" internal thread	JWL.627244
1/2" ext. x 1/2" int. x 1/2" internal thread	JWL.627255



X- STUK

afmetingen (mm)	Ref.
4 x 1/8" internal thread	JWL.628000
4 x 1/4" internal thread	JWL.628022
4 x 3/8" internal thread	JWL.628044
4 x 1/2" internal thread	JWL.628055



VERBINDINGSSTUK VOOR SLANG

afmetingen (mm)	Ref.
3/16" - 5 mm x 1/8" external thread	JWL.625000
3/16" - 5 mm x 1/4" external thread	JWL.625002
1/4" - 6 mm x 1/8" external thread	JWL.625020
1/4" - 6 mm x 1/4" external thread	JWL.625022
1/4" - 6 mm x 3/8" external thread	JWL.625024
1/4" - 6 mm x 1/2" external thread	JWL.625025
5/16" - 8 mm x 1/4" external thread	JWL.625032
5/16" - 8 mm x 3/8" external thread	JWL.625034
5/16" - 8 mm x 1/2" external thread	JWL.625035
3/8" - 10 mm x 1/4" external thread	JWL.625042
3/8" - 10 mm x 3/8" external thread	JWL.625044
3/8" - 10 mm x 1/2" external thread	JWL.625045
1/2" - 13 mm x 1/4" external thread	JWL.625052
1/2" - 13 mm x 3/8" external thread	JWL.625054
1/2" - 13 mm x 1/2" external thread	JWL.625055
1/2" - 13 mm x 3/4" external thread	JWL.625057
3/4" - 20 mm x 3/8" external thread	JWL.625074
3/4" - 20 mm x 3/4" external thread	JWL.625077
1/4" - 6 mm x 1/8" internal thread	JWL.626020
1/4" - 6 mm x 1/4" internal thread	JWL.626022
1/4" - 6 mm x 3/8" internal thread	JWL.626024
5/16" - 8 mm x 1/4" internal thread	JWL.626032
3/8" - 10 mm x 1/4" internal thread	JWL.626042
3/8" - 10 mm x 3/8" internal thread	JWL.626044
3/8" - 10 mm x 1/2" internal thread	JWL.626045
1/2" - 13 mm x 1/4" internal thread	JWL.626052
1/2" - 13 mm x 3/8" internal thread	JWL.626054
1/2" - 13 mm x 1/2" internal thread	JWL.626055



SCHROEFDRAADBUS

afmetingen (mm)	Ref.
1/8" internal thread x 1/8" internal thread	JWL.629000
1/8" internal thread x 1/4" internal thread	JWL.629002
1/8" internal thread x 3/8" internal thread	JWL.629004
1/4" internal thread x 1/4" internal thread	JWL.629022
1/4" internal thread x 3/8" internal thread	JWL.629024
1/4" internal thread x 1/2" internal thread	JWL.629025
3/8" internal thread x 3/8" internal thread	JWL.629044
3/8" internal thread x 1/2" internal thread	JWL.629045
1/2" internal thread x 1/2" internal thread	JWL.629055
3/4" internal thread x 1/2" internal thread	JWL.629075
3/4" internal thread x 3/4" internal thread	JWL.629077



VERBINDINGSSTUK VOOR SLANG

afmetingen (mm)	Ref.
1/4" (6mm) x 1/4" (6mm)	JWL.621022
5/16" (8mm) x 5/16" (8mm)	JWL.621033
3/8" (10mm) x 3/8" (10mm)	JWL.621044
1/2" (12mm) x 1/2" (12mm)	JWL.621055